ID AUTO GATE

POWERTECH

A Best Choice for your home Automation

DESIGNED FOR RESIDENTIAL APPLICATION

KIT PW320/PW330

SWING GATE OPENERS

ระบบบานเปิด

250/350กก.(ต่อบาน)

"พร้อมระบบชะลอความเร็วในการเปิดปิด"

Specifications	PW320	PW330
Gear Type	Worm gear	Worm gear
Max Absorbed Power	144W	144W
Peak Thrust	3000N	3500N
Nominal Thrust	2500N	3000N
Stroke Length	356mm with mechanical stopper 400mm without mechanical stopper	350mm
Power Supply	24V DC	24V DC
Nominal Input Power	3A	3A
Maximum Gate Weight	250 kg per leaf	350 kg per leaf
Maximum Gate Length	3 meters	4 meters
Operating Temperature	-20°C~+50°C	-20°C~+50°C
Dimension	819mm * 115mm * 106mm	844mm * 115mm * 106mm
Weight	6.0kg	6.25kg

www.idautogate.com

DESIGNED FOR RESIDENTIAL APPLICATION

KIT PW320/PW330
SWING GATE OPENERS

PW320 Gear Motor

PW330 Gear Motor

PW330L Gear Motor

- PW320: Maximum weight / length per gate leaf: 250kg / 3m.
- PW330: Maximum weight / length per gate leaf: 350kg / 4m.
- PW330L: Maximum weight / length per gate leaf: 500kg / 5m.
- 24V DC electro-mechanical gear motor for residential use.
- Worm gear provides durability and silence in motor operation.
- Hall sensor imbedded in the gear motor for easy system learning.
- Slowdown during the end of opening and closing phase.
- Single-gate or dual-gate installation is optional.

PC200 Control Box

- Two back-up batteries (2.2A) for power failure operation
- Incorporated radio receiver can be matched with 200 transmitters.
- Safe design to prevent PCB burned for wrong wiring connection.
- Four setting of motor torque adjustment.
- Over-current function meets European safety requirements.
- Modern appearance and easy installation.
- Seven modes of gate auto-closed setting.

PF-1 Flashing Light

- Convenient horizontal and vertical installations.
- Stylish shape and fashionable appearance.
- 24V halogen bulb offers excellent illumination and long lifetime.

PR-1 2-Channel Transmitter

- Rolling code 433MHZ transmitter.
- 30 meters transmitting distance.
- Two buttons for single-gate or dual-gate operation.

PKS-1 Key Selector

- Eye-catching appearance for outdoor installation.
- Two keys attached with the key selector to open the gate without the transmitter.

PPB-1 Push Button

- Easy opening for indoor use.
- Novel design of the appearance for opening the gate without the transmitter.

PH-1 Photocells

- IP66 water proof for outdoor environment use.
- Long sensing distance for 30 meters.
- AC/DC 12~24V application.

PEL-1 Electric Latch & Stopper

- 24V DC latch for additional safety of the gate.
- Release key to unlock the latch when there is a power failure.

PRB-1 Receiver Box

- Rolling code 433MHz receiver box.

PR-2 4-Channel Transmitter

- Rolling code 433MHz transmitter.
- 30 meters transmitting distance.
- Four buttons for gate or receiver box operation.

ID AUTO GATE
POWERTECH

ID AUTO GATE (HEAD OFFICE)
99/99 หมู่ 7 ถนนจตุโชติ แขวงออเงิน
เขตสายไหม กรุงเทพ 10220
Tel : 02-156-9999
Mobile : 093-416-3646
Mobile : 095-329-6442
www.idautogate.com

ภาคใต้ (ภูเก็ต)
Tel : 076-524-500

ภาคเหนือ
Tel : 094-3289788

ภาคตะวันออก/ตะวันออกเฉียงเหนือ
Tel : 087-5551124, 083-555-1585

ภาคตะวันตก
Tel : 089-555-1575, 081-904-4387